

| Gwint całowy zwykły Whitwortha BSW, BS-84:2007 | | | | | | | | 800 | | | | |
|---|-------|----|-------|---------|---|-------|------|----------------|--|--|--|--|
| | | | | | | | | | | | | |
| Rodzaj materiału obrabianego | | | | | | | | P M K N S H | | | | |
| Wykonanie | | | | | | | | | | | | |
| Rodzaj materiału | | | | | | | | HSS | | | | |
| Nakrój | | | | | | | | 1,75P | | | | |
| | | | | | | | | Norma | | | | |
| | | | | | | | | DIN-EN 22 568 | | | | |
| | | | | | | | | Tol. | | | | |
| | | | | | | | | medium | | | | |
| | | | | | | | | INDEX | | | | |
| | | | | | | | | N1-121001 | | | | |
| 1/8 - 40 | 3,18 | 40 | 0,635 | 20 x 5 | 3 | 3,09 | 7123 | ● | | | | |
| 3/16 - 24 | 4,76 | 24 | 1,058 | 20 x 7 | 4 | 4,66 | 7125 | ● | | | | |
| 1/4 - 20 | 6,35 | 20 | 1,270 | 20 x 7 | 4 | 6,24 | 7127 | ● | | | | |
| 5/16 - 18 | 7,94 | 18 | 1,411 | 25 x 9 | 4 | 7,82 | 7128 | ● | | | | |
| 3/8 - 16 | 9,53 | 16 | 1,588 | 30 x 11 | 4 | 9,40 | 7129 | ● | | | | |
| 7/16 - 14 | 11,11 | 14 | 1,814 | 30 x 11 | 4 | 10,98 | 7130 | ● | | | | |
| 1/2 - 12 | 12,7 | 12 | 2,117 | 38 x 14 | 4 | 12,56 | 7131 | ● | | | | |
| 9/16 - 12 | 14,29 | 12 | 2,117 | 38 x 14 | 4 | 14,14 | 7132 | ● | | | | |
| 5/8 - 11 | 15,88 | 11 | 2,309 | 45 x 18 | 5 | 15,72 | 7133 | ● | | | | |
| 3/4 - 10 | 19,05 | 10 | 2,540 | 45 x 18 | 5 | 18,89 | 7135 | ● | | | | |
| 7/8 - 9 | 22,23 | 9 | 2,822 | 55 x 22 | 5 | 22,10 | 7137 | ● | | | | |
| 1 - 8 | 25,4 | 8 | 3,175 | 55 x 22 | 5 | 25,27 | 7139 | ● | | | | |

